



Skafander Collection

Reference	SKF 46 DV SC DT TTNRBR 5N (NR)
Case	Skafander case Water resistant up to 100 meters Diameter: Ø 45.3 mm x Thickness: 10.1 mm Width: 45.8 mm x Length: 57 mm x Thickness: 15.6 mm Black inserts on both sides of the case Sapphire crystal
Functions	Hours, Minutes, Date, Diving Timer
Instructions	Winding shaft with 2 positions: 1.Winding. 2.Time setting. Lock button at 9 o'clock to lock/unlock the push-buttons Push-button at 10 o'clock to start the minutes counter 1/1 Push-button at 8 o'clock to start the minutes counter 5/5
Movement	MVD FM 2800-SK Self-winding movement with bidirectional rotor system Power reserve of 42 hours 241 components 25 jewels Diameter: Ø 31.5 mm. Thickness : 5.69 mm Balance wheel frequency set at 28,800 alternations per hour
Movement Decoration	Côtes de Genève and brushing "soleil papier" on the bridges and the rotor Circular graining on the two sides of the main plate Chamfering of the bridges 24k gold bath and rhodium plating of the components 24k gold finish on the written engravings Circular brushing of the rotor ball bearing Brushing "soleil papier" on the barrel Polishing at 45° and brushing "soleil" of the ratchet Polished and blued screws
Bracelet	Caoutchouc strap
Buckle	Brushed grade-2 titanium folding buckle Brushed folding buckle Black PVD coating Lid in 18k rose gold with Franck Muller emblem

